



stratasys



# Neo<sup>®</sup>800+ 3D Printer

The new benchmark for high-speed, large-format SLA



## Designed by Engineers, for Engineers.

The Neo<sup>®</sup>800+ 3D printer combines cutting-edge software and advanced technology to deliver up to **50% faster performance** than its predecessor. With enhanced part fidelity and reliability, it minimizes downtime and service needs, setting a new standard for large-format SLA printing with the **lowest total cost of ownership**.

### System Specifications

|                          |                     |  |
|--------------------------|---------------------|--|
| Laser & Scanning System  | Laser               | 4 Watt, 355 nm, solid-state frequency tripled Nd:YVO <sup>4</sup>  |
|                          | Beam Focus          | Dynamic & Variable   |
|                          | Beam Size           | 120 to 750µm   |
|                          | Scanning Speed      | Up to 790 in./s (20 m/s)   |
| Layer Resolution         |                     | 50 to 200 µm*  |
| Minimum Feature Size     |                     | 0.007 in. (0.17 mm) in X & Y <sup>†</sup><br>0.016 in. (0.4mm) in Z <sup>†</sup>   |
| Build Modes              |                     | High Detail & Standard Detail (HD & SD)  |
| Accuracy                 |                     | Dimension <3.94 in. ±0.004 in.; Dimension >3.94 in. ±0.15% <sup>†</sup><br>Dimension <100 mm ±0.1 mm; Dimension >100 mm ±0.15% <sup>†</sup>  |
| Material Compatibility   |                     | Open resin system – compatible with commercially available 355 nm stereolithography resins   |
| Capacities               | Build (XYZ)         | Half: 31.50 x 31.50 x 11.81 in. (800 x 800 x 300 mm)<br>Full: 31.50 x 31.50 x 23.62 in. (800 x 800 x 600 mm)   |
|                          | Vat Fill            | Half: 83 US gal (780 lb <sup>†</sup> ) [316 ltr (354 kg <sup>†</sup> )]<br>Full: 147 US gal (1378 lb <sup>†</sup> ) [558 ltr (625 kg <sup>†</sup> )]   |
| Software                 | Operating System    | Windows 10 IoT Enterprise LTSC 2021  |
|                          | Input File Format   | SLC  |
|                          | Control Software    | Titanium   |
|                          | Build Prep Software | GrabCAD or Materialise Magics  |
|                          | Remote Editor       | Titanium Assistant (Optional)  |
| Connectivity             | Ethernet            | Fully compliant with IEE 802.3, IEEE 802.3u, IEEE 802.3ab  |
|                          | USB Port            | USB 3.1  |
| Features & Build Options |                     | Build validation / Build time estimator / Material usage estimator / Scheduled start / Open build parameters enabling any material to be processed / On-the-fly parameter adjustment and part deletion / Upper surface build quality optimization / Bubble remover with automated option |



## System Specifications

|  |                              |  |
|--|------------------------------|--|
| <b>Advanced Services &amp; Reporting Tools</b> |                              | Industry 4.0 compliant / Full part traceability / Logging of machine utilization; build history; parameters; material usage; formatted data export / System and build status email notification § / Onboard camera / Resin viscosity tracking / User level access control / Scheduled lighting |
| <b>Support</b>                                 |                              | 1-click "snapshot" job diagnostic pack for remote support / Remote diagnostics §   |
| <b>Electrical Requirements</b>                 | <b>208 ~ 240 V, 50/60 Hz</b> | 900 W Typical operation, 1900 W Max  |
| <b>Environmental Requirements</b>              |                              | Temperature range: 68-74 °F (20-23 °C), max rate change ±2 °F/hr (1 °C/hr)<br>Relative humidity 20-50% non-condensing  |
| <b>UPS</b>                                     |                              | 1 – 2 hrs of system up-time with intelligent UPS control***  |
| <b>Dimensions (WxDxH)</b>                      | <b>Printer (uncrated)</b>    | 53.2 x 64.2 x 90.6 in. (1,350 x 1,630 x 2,300 mm)  |
|  | <b>Printer Crated</b>        | 67.3 x 73.2 x 100.8 in. (1,710 x 1,860 x 2,560 mm)   |
|  | <b>Vat (uncrated)</b>        | 46.9 x 35.9 x 34.3 in. (1,190 x 910 x 870 mm)  |
|  | <b>Vat Crated</b>            | 55.2 x 41.4 x 43 in. (1,400 x 1,050 x 1,090 mm)  |
| <b>Weight</b>                                  | <b>Printer</b>               | 1,764 lb (800 Kg)  |
|  | <b>Vat</b>                   | 529 lb (240 Kg)  |
| <b>Crated Weight</b>                           | <b>Printer</b>               | 2,646 lb (1200 Kg)   |
|  | <b>Vat</b>                   | 960 lb (435 Kg)  |
| <b>Warranty</b>                                | <b>System</b>                | 12 months on-site service and support, as per Stratasys conditions of sale   |
| <b>Accessories</b>                             | <b>UV800</b>                 | 1,058 lb (480 Kg)  |
|  | <b>Unload Cart</b>           | 463 lb (210 Kg)  |
| <b>Regulatory Conformity</b>                   |                              | CE UK FC KC A  |

\* 100µm layer parameters are supplied for Stratasys certified materials. Parameters for alternative thicknesses may be available. Layer thickness range is material dependent. Contact Stratasys for more details.

† Accuracy and minimum feature size will vary depending on material, parameters, part geometry and size, pre- and post-processing methods and environment.

‡ Based on typical material density, 2.47 lb/0.3 gal @ 78.8 °F (1.12kg/ltr @ 26 °C).

§ Internet connection is required for full or partial functionality.

\*\* Specification can be subject to change without prior notice.

\*\*\* When connected to a Stratasys Certified UPS, not sold with the Neo800+ 3D printer, please contact Stratasys for further details.



alphacam GmbH  
Erlenwiesen 16  
D-73614 Schorndorf  
Tel.: +49 7181 9222-0  
info@alphacam.de

alphacam austria GmbH  
Handelskai 92, Gate1 / 2. OG / Top A  
A-1200 Wien  
Tel.: +43 1 3619 600-0  
info@alphacam.at

alphacam swiss GmbH  
Zürcherstrasse 14  
CH-8400 Winterthur  
Tel.: +41 52 26207-50  
info@alphacam.ch



alphacam.de  
.at  
.ch

stratasys.com

ISO 9001:2015  
Certified

PRODUCT SPEC SHEET  
SLA



©2025 Stratasys. All rights reserved. Stratasys, the Stratasys Signet logo, Neo, Neo800, Neo800+, ScanControl+, Somos, PerFORM, WaterShed Black and WaterShed XC+ are trademarks or registered trademarks of Stratasys Ltd. and/or its subsidiaries and affiliates. All other trademarks are the property of their respective owners. PSS\_SL\_Neo800Plus\_0625a